Technical Data Sheet Issue: 06-10-2015



FIX-O-FLEX HAFTGRUND

Properties:	FIX-O-FLEX HAFTGRUND is a solvent-containing cleaning agent for surfaces where FIX-O-FLEX adhesion and sealing compounds will be applied.		
	FIX-O-FLEX HAFTGRUND and oily residues.	TGRUND is dust binding and cleans surfaces with greasy	
Technical data:	<u>Substance data:</u> Consistency Colour Odour Spec. density (23°C) Dyn. viscosity (23°C) Processing temperature	liquid colourless of ethanole approx. 0.79 g/cm ³ approx. 6 mPas 5 - 30°C	DIN EN ISO 2811-1 DIN EN ISO 2555 substrate temperature
Decession			
Processing:	<i>FIX-O-FLEX HAFTGRUND</i> is evenly applied on the surface. Once the residues are slightly loosened they are removed with an absorbent cloth whipped off.		
	This should be repeated until the surface is completely clean.		
Safety information:	<i>FIX-O-FLEX HAFTGRUND</i> is classified as hazardous according to Regula (EC) 1272/2008 (CLP). Danger: Highly flammable liquid and vapour.		
	It is therefore necessary, before beginning processing, to become familiar with the precautions and safety advice as indicated in the material safety data sheet.		
Packaging:	500 ml tin 1000 ml tin		
	Bigger packaging on request.		
Storage:	Shelf life at least 12 month in original packaging when stored in dry conditions between 15-25°C, protected from heat, frost and direct sunlight. After the expiration the use of the product is generally not recommended, unless an approval has been provided by TPH. This approval can only be obtained by the quality assurance department of TPH releasing the material after verification of main properties being within specification.		
Disposal:	sal: Small quantities of cured product residues can be disposed of as norm domestic waste. Dispose of not cured product components must be effect in accordance with the corresponding local regulations. For further information please refer to the material safety data sheets.		



Legal notice:

The correct and thus successful application of our products is not subject to our control. A guarantee can be issued for the quality of our products within the framework of our sales and supply conditions, however not for successful processing. All data and specifications in this specification sheet are based on the present state of the art and the right to changes and adaptations for the sake of development remains explicitly reserved. The consumption specifications designated by us can be only average empirical values, where deviations are possible on an individual basis and therefore cannot be excluded by us.

TPH Bausysteme GmbH Nordportbogen 8 D-22848 Norderstedt

 Tel.:
 +49 (0)40 / 52 90 66 78-0

 Fax:
 +49 (0)40 / 52 90 66 78-78

 e-mail
 info@tph-bausysteme.com

 Web
 www.tph-bausysteme.com

